

Why is **SUBMIT** the **Ultimate** Way to Cut Through Grease and Waste in Drains and on Hard Surfaces?

- **SUBMIT Grease and Waste Digester** is a powerful bacterial formula
- 100 Billion CFU/Gallon. Multi-Strain.
- Resists hot water up to 200° F
- No caustics, acids, solvents, or free enzymes
- Neutralizes foul odors

Bioengineered Bacterial Formula

SUBMIT Grease & Waste Digester incorporates a superior blend of biodegradable surfactants and odor counteractants with five strains of non-pathogenic bacterial spores. Our exclusive blend of bioengineered bacteria has the ability to withstand hot water temperatures (up to 200°F) and is resistant to chlorinated products, disinfectants, bleach, and acidic or alkaline conditions.

SUBMIT Grease & Waste Digester is specifically designed for treatment and maintenance of drains and grease traps, as well as augmentation of bacterial stains in septic tanks. Use in wastewater treatment plants on organic waste solids, such as screenings, grit sludge, and scum removing to counteract odors.

SUBMIT Grease & Waste Digester is acceptable under former USDA guidelines for use in inedible product processing areas, non-processing areas, and exterior areas of official establishments operating under the Federal meat, poultry, shell egg grading, and egg products inspection programs.

Directions for Use

Shake well before use. Use at night or during off hours to allow sufficient time to establish bacterial colonies in use.



ORGANIC WASTE TREATMENTS - DRAIN LINES: Pour 1.5 oz per inch of pipe diameter directly into drain pipe. Use product twice per week, or as needed depending on system problems. **INITIAL TREATMENT:** Begin with the lowest floor and continue with one floor per day until top floor is reached. Then use only on the top floor.

TOILETS AND URINALS: On a regular basis, treat toilets, urinals, and sink drains with 1 ounce of product. Apply at the end of the business day, giving ample time for product to work.

GREASE TRAPS: Pour 1-3 oz. per 100 gallons (13 cu.ft.) into a sink or drain line closest to trap. Use product daily. **INITIAL TREATMENT:** Pump or pour 32 oz. per 100 gallons (13 cu.ft.) to produce a purge treatment. For best results, grease trap should be pumped out prior to starting treatment.

SEPTIC TANKS: Flush 8 oz. per 500 gallons (65 cu.ft.) down toilet. **INITIAL TREATMENT:** Pour 32 oz per 500 gallons (65 cu.ft.) to purge treatment.

ODOR CONTERACTANT: Use a sprayer to saturate solids. Apply as needed to counteract odors.



Case of
(4) 1 gallon
#SGWD-1



Submit Grease & Waste Digester

Ready-to Use
For Foodservice, Industrial,
Institutional and Municipal Use

Safety Precautions

CAUTION: May cause slight eye irritation. Avoid contact with eyes, skin, open wounds, or clothing. Wash thoroughly with soap and water after handling.

Keep out of the reach of children.

First Aid

IF IN EYES: Flush with plenty of water. Get medical attention if irritation persists.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation persists.

IF SWALLOWED: Call a physician or poison control center. Drink 1-2 glasses of water. Induce vomiting only if advised by a physician.

IF INHALED: Move to fresh air.

Ingredients

Ingredients	CAS#
Water	7732-18-5
Bacterial Spores	1395-21-7
Fatty Diethanolamide	Mixture
Sodium alpha-olefin sulfonate	69439-57-6
Propylene Glycol	57-55-6
Essential Oils	Mixture
Borax	1303-96-4
DYE	Mixture
VOC's	0%

See the Material Safety Data Sheet (MSDS) for more information

HMIS RATINGS	
1	Health
0	Flammability
0	Reactivity

4=Severe, 3=Serious, 2=Moderate,
1=Slight, 0=Minimal Hazard

To Order

Description	Part Number
Submit Grease and Waste Digester - Case of (4) 1 gallon / 3.78L	SGWD-1



31 Columbus Avenue
Englewood, NJ 07631
Phone (888) 564-3204
FAX (201) 568-1977
www.ultimatesolutionsinc.net