

## **HOW TO USE 3 GALLON SPOTTER**

1. Remove spotter from box
2. Place on level surface.
3. Open rotating lock on back of machine and remove top tank (recovery tank) from bottom tank (solution tank). You have to tip tank to allow it to come free of bottom tank.
4. Fill bottom tank with about a quart of water.
5. Replace top tank by tipping front of tank to allow it to connect with bottom tank, center tank properly and then close rotating lock at back to secure in place.
6. Plug unit into a ground electrical outlet.
7. Attach solution hose to unit: Hold female quick disconnect (female QD) on hose and slide collar back on female QD. Slide on to male quick disconnect (male QD) on machine. Release collar of female QD. You should hear hose click into place. If you do not hear it click into place repeat previous steps.
8. Secure vacuum hose securely onto drain spout on front of recovery tank. You may have to force vacuum hose on by turning it back and forth while pushing hose onto drain spout. If tool is not connected to hoses, repeat procedures to attach tool to hoses.
9. Turn on pump only and depress trigger on tool to flush the antifreeze completely from unit.
10. After flushing antifreeze from unit, remove top tank, fill bottom tank with desired amount of clean water only (highly recommended), leaving water level at least 4" from top. Do not over fill.
11. Tip solution tank into sink or drain if overfilled or to empty tank after use.
12. Pre-spray a small section of carpet with carpet cleaning solution. Agitate with brush. Allow it to dwell a few minutes before extraction begins.
13. For a heated unit, turn on heater for about 3 minutes to preheat water.
14. For cold or heated spotters, turn on pump and depress trigger on tool to begin spraying solution to carpet. Agitate carpet with end of tool. Then alternate spraying solution and vacuuming. Alternating spraying and vacuuming will allow heater to keep water at optimal temperature. \*\*Caution, brass QD's can get hot. Allow to cool before disconnecting.
15. If you are not spraying solution for more than a few minutes, turn off heater. Water should remain hot. When you begin to spray solution again, turn heater back on.

**TOGETHER WE'RE BETTER!**

16. Listen for any changes to the vacuum motors. When recovery tank fills, the yellow vacuum restrictor slides up pipe to partially block air. The sound of the motor will be different and this is notice to shut off machine completely and empty recovery tank. Failure to stop at this point will void warranty, as water will be sucked into vacuum motors.
17. Remove top tank from unit, open hatch on top by unscrewing counter clockwise to allow air in and tip and pour recovered solution into a sink, toilet or drain.
18. Close top hatch by screwing it on clockwise, fill bottom tank if necessary, reattach top tank to unit and continue cleaning.



**TOGETHER WE'RE BETTER!**